



# GKB Renovator



Do you encounter any problems with a compacted synthetic turf pitch? Is the compacted infill layer responsible for a reduced water permeability? Together with the Renovator we are able to provide you the solution.



You are able to adjust the operating depth by turning in or out the two adjustable legs. The rubber wheels ensure that the Renovator will softly roll across the synthetic turf pitch. The machine is powered by a power-take off shaft (PTO). Since we are an advocate of soundness, the entire powering system is executed in a robust manner.

Together with the Renovator you are in possession of a robust and reliable synthetic turf maintenance machine. Five rotating brushes form the foundation of the machine. Because the brushes hoke in each other, you will not miss a single inch when you are operating on your pitch. The infill material will be situated on the pitch after the operation. Following you can use the Quick-Brush to brush in the infill. Furthermore, it is also possible to use the GKB Infill Remover to dispose the material.


**THE WORKER IS KING**



# Renovator

*Specifications:*

<i>Type</i>	RV160
<i>Working width</i>	160 cm / 63"
<i>Working depth</i>	0 - 5 cm / 0 - 2"
<i>Dimensions (l x w x h)</i>	90 x 180 x 110 cm / 35 x 71 x 43"
<i>Weight</i>	240 kg / 530 lbs
<i>Power requirement</i>	30 - 45 hp
<i>Linkage</i>	Standard three-point hitch cat I - II



**THE WORKER IS KING**